



ENHANCED RELIABILITY

Carriers can hold several gauges (Quartz or Piezoresistive).
Human error reduced thanks to its simplicity.

METROLOG BREAKTHROUGH

Pressure measurement point with a buffer system to reduce gas ingress.
Gauges protected and insulated from vibrations.
Easy-to-use gauge carrier operated by anyone in less than 10 mins.

APPLICATIONS

SlickLine operations for long term jobs in hostile environments.
Protection of 3/4" and 1 1/4" gauges in standard operations.
1" gauge carriers for 1 iGauges or 1 iQuartz, for operations in 1"660 or 1"315 tubing

SPECIFICATIONS

MECHANICS

Material	Stainless steel (parkerised)			
Sour service	NACE recommendations			
Threads	15/16" 10 UNC (pin up x box down), 5/8" 11 UNC or others			

TYPE

	For iGauge	For iQuartz	For CGM	For PRM
Length	2 ft.	4 ft.	4.5 ft.	4 ft.
Diameter	1 1/4"	1 1/4"	1"11/16"	1"11/16"

Metrolog, a Sercel Brand

1110 Avenue l'Occitane, Technoparc, Bât.2, C.S. 17619. 31676 Labège Cedex FRANCE

Telephone: (33) 5 61 34 80 74. Fax: (33) 5 61 20 41 31. E-mail: sales@metrolog.com

www.metrolog.com

Sercel

S.A. au capital de 2 000 000 €. Siège Social: 16 rue de Bel-Air 44470 Carquefou.

378.040.497 R.C.S. Nantes. Code APE 2651B

www.sercel.com

Printed in France. © Sercel 06/13 - Information subject to change without notice. TDSO_026_B